



## DEEP CLEAN 250

### HUNDREDS OF INDUSTRIAL, COMMERCIAL, AND RESIDENTIAL USES

<p><b>Concrete</b>  <b>Industrial Floors</b>  <b>Commercial Kitchens</b>  <b>Stamped Concrete</b>  <b>Auto Repair Shops</b></p>	<p><b>Food Service Agencies</b>  <b>Masonry</b>  <b>Machine Shops</b>  <b>Driveways</b>  <b>Tile Floors</b></p>	<p><b>Parking Garages</b>  <b>Stone</b>  <b>Gas Stations</b>  <b>Pool Decks</b>  <b>Freezer Floors</b></p>	<p><b>Engines</b>  <b>Mobile Washers</b>  <b>Trucking</b>  <b>Companies</b></p>
---	---	--	---

**PLEASE READ THIS SHEET CAREFULLY BEFORE YOU START TO APPLY DEEP CLEAN !**

### PRODUCT DESCRIPTION

**DEEP CLEAN 250 HEAVY DUTY DEGREASER** is a non-toxic, fortified, concrete and multipurpose cleaner that is designed to clean and “etch” the surface simultaneously. Oils, dirt, efflorescence, and grime are removed. The primary use is to remove deeply penetrated oil stains and contaminated surface residue.

**DEEP CLEAN 250 HEAVY DUTY DEGREASER** may be used full strength as an environmental alternative to muriatic and other acids for surface preparation and basic cleaning. Architectural features are enhanced by removing the gradual build-up of atmospheric grime.

### PRODUCT BENEFITS

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>*Biodegradable</li> <li>*Easy shipping and handling</li> <li>*Non-toxic</li> <li>*High alkalinity for tough soils &amp; grease</li> </ul> | <ul style="list-style-type: none"> <li>*No streak rinse</li> <li>*USDA approved</li> <li>*Will penetrate Diesel smoke on trailers</li> </ul> |
|--|--|

### APPLICATION

For best results, do not dilute product or pre-wet surface. Prior to cleaning the entire surface, apply **DEEP CLEAN 250** to heavily saturated or hard to clean areas. Apply as needed and allow to “etch” the surface for approximately thirty (30) minutes. Rinse with clean water. Repeat as needed. See label for detailed directions.

### INTERIOR APPLICAIIONS

Interior cleaning is usually accomplished in a controlled manner. Normally DEEP CLEAN 125 is applied sparingly to facilitate easier clean-up, unless the interior surface can be rinsed with high pressure water similar to an exterior surface. Normal care and protection procedures should be followed when working indoors.



**RECOMMENDED DILUTION**

A test patch is the best method to determine proper dilution rates. Full strength applications may damage sensitive architectural surfaces, but may be required for hard to clean areas.

**MANUFACTURER’S GUARANTEE**

DEEP CLEAN IS GUARANTEED TO PERFORM AS REPRESENTED WHEN USED AS DIRECTED. IF THE PURCHASER IS NOT SATISFIED THE MANUFACTURER WILL FURNISH, WITHOUT CHARGE, SUFFICIENT PRODUCT FOR ANOTHER APPLICATION.

**PROPERTIES**

Form .....	Liquid	Weight .....	8.8 lbs. Per gallon
pH .....	See MSDS Sheet	Specific Gravity .....	See MSDS Sheet
Flash Point .....	None	Toxicity .....	None
Color .....	Dark Red		

**TEST SAMPLE**

A test patch is always recommended prior to cleaning architectural surfaces. Some surface damage may result from full strength application.

**SAFETY**

Refer to : Material Safety Data Sheet regarding hazards and personal protection.

**RECOMMENDED PRODUCTS**

- Evercrete Deep Penetrating Sealer  
Concrete Preserver/Sealant
- Evercrete Top Sealer  
Superior Masonry Top Sealer
- Everwood  
Outstanding Wood Preserver
- Deep Clean 125  
Domestic Grade Degreaser

**EVERCRETE DEALER**